

dot-spot

*Akzente setzen!*

eco230 

# eco230

efficient LED technology  
with long operating life

Mounting bracket and ground spike  
made from V4A stainless steel -  
corrosion-proof and non-breakable

## The top-class „plug and play“-solution!

The **eco230** offers a unique atmosphere as well as safety in gardens, residential and business buildings, for the 230 V LED spot operates completely without external power supply. Simply fix the **eco230** in the desired position using the mounting bracket and the ground spike, insert the plug into the socket, done! With only 6 W, the LED of the **eco230** generates a remarkable light output of more than 400 lumen.

### Sustainability and environmental protection start with quality products:

The **eco230** is manufactured in Germany, it is waterproof and features a turned, silver anodized housing. Mounting bracket and ground spike are made from corrosion-proof and non-breakable stainless steel. The integrated high-output LED offers a service life of more than 40,000 hours.

turned aluminium housing,  
silver anodized

5m connection cable  
with mains plug

### Application areas

- Tree and plant lighting
- Facade and object lighting
- Lighting in monument protection
- Pathway lighting
- Architecture and garden accentuation
- Event lighting

### Your advantages

- plug and play - all you need is a socket
- easy ground spike installation
- high-quality materials, made in Germany
- rotatable and pivotable at the mounting bracket
- energy-saving and durable LED technology

230 V AC

plug & play

LED 6 W

warmwhite

2700 K

408 lm

IP 67



### Technische Daten

|                                    |   |                                      |
|------------------------------------|---|--------------------------------------|
| Anwendung                          | Objekt- und Gartenstrahler - <i>object- and garden spot</i>   | <i>usage</i>                         |
| Spannung / Leistung                | 230 V 50 Hz / 6 W LED   | <i>voltage / power consumption</i>   |
| Lichtleistung LED / Abstrahlwinkel | 408 Lumen - <i>lumen</i> / 35°                                | <i>light output LED / beam angle</i> |
| Anschluss                          | 5m Gummi-Kabel mit Stecker - <i>5m rubber cabel with plug</i> | <i>connection</i>                    |
| Schutzart / Schutzklasse           | IP 67 / I   | <i>IP rate / protection class</i>    |
| Gehäuse                            | eloxiertes Aluminium - <i>anodized aluminum</i>               | <i>housing</i>                       |
| Abmessungen                        | Ø 64 x 70 mm  | <i>dimensions</i>                    |

dot-spot  
*Akzente setzen!*

dot-spot GmbH & Co. KG  
Industriestraße 1A  
90592 Schwarzenbruck

Fon: +49 (0) 9128 / 72 22 17 - 0  
Fax.: +49 (0) 9128 / 72 22 17 - 9  
service@dot-spot.de  
www.dot-spot.de