



**Special features**

- Adjustable colour temperature
- High colour reproduction value
- Swivel-mounted

<b>Housing Material</b>	Aluminium
<b>Housing Color</b>	White
<b>Material of Lens</b>	Glass
<b>Colour of Lens</b>	White
<b>Functions</b>	HCL
<b>Protection Class</b>	Protection class III/safety extra-low voltage
<b>Operating Mode</b>	Constant voltage
<b>Rated Input</b>	8 W
<b>Rated Power Consumption Standby</b>	0.5 W
<b>Rated Input Voltage</b>	24 V/DC
<b>Power Supply Unit incl.</b>	No
<b>Connection Cable Secondary</b>	Yes
<b>Secondary Connection</b>	Open cables
<b>Secondary Cable Length</b>	0.24 m
<b>Dimmable</b>	Yes
<b>Control</b>	Dimmable via optional controller
<b>Motion Detector</b>	No

<b>Height</b>	46 mm
<b>Diameter</b>	78 mm
<b>Installation Depth</b>	60 mm
<b>Cut Out Diameter</b>	68 mm
<b>Product weight</b>	116 g
<b>Working Temperature</b>	-5 to 40 °C
<b>Storage Temperature</b>	-10 to 60 °C
<b>IP Protection Class</b>	IP 20
<b>Life Time L70 / B50</b>	50000 h
<b>Switching Cycles</b>	100000
<b>Power Consumption EEI</b>	8 kWh/1000h G

<b>Light Source</b>	LED, Light source not changeable
<b>Colour Temperature</b>	2500-6500 K
<b>Colour Consistency</b>	6 SDCM
<b>Colour Rendering Index (Ra)</b>	80
<b>Rated Luminous Flux</b>	534 lm
<b>Luminous Efficiency</b>	66.8 lm/W
<b>Rated Angle of Reflection</b>	65 Degree
<b>Light Distribution</b>	Symmetric
<b>Distribution Characteristic 120°</b>	DLS
<b>Swivel Angle</b>	25 Degree
<b>Light Exit Surfaces</b>	1
<b>Light characteristics</b>	Direct
<b>Light direction</b>	Below

