



Housing Material	Aluminium
Housing Color	White
Material of Lens	Glass
Colour of Lens	White
Functions	HCL
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant voltage
Rated Input	16 W
Rated Power Consumption Standby	0.5 W
Rated Input Voltage	24 V/DC
Power Supply Unit incl.	No
Connection Cable Secondary	Yes
Secondary Connection	Open cables
Secondary Cable Length	0.2 m
Dimmable	Yes
Control	Dimmable via optional controller
Motion Detector	No

Height	65 mm
Diameter	108 mm
Installation Depth	70 mm
Cut Out Diameter	95 mm
Product weight	407 g
Working Temperature	-20 to 60 °C
Storage Temperature	0 to 0 °C
IP Protection Class	IP 20
Life Time L70 / B50	50000 h
Switching Cycles	50000
Power Consumption EEI	15 kWh/1000h G

Light Source	LED, Light source not changeable
Colour Temperature	2500-6500 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	1118 lm
Luminous Efficiency	69.9 lm/W
Rated Angle of Reflection	65 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS
Swivel Angle	25 Degree
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

