



Special features

- Swivel-mounted
- High colour reproduction value

Housing Material	Aluminium
Housing Color	White
Housing Surface	Matt
Material of Lens	Glass
Surface Structure of Lens	Satined
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant voltage
Rated Input	16 W
Rated Power Consumption Standby	0.5 W
Rated Input Voltage	24 V/DC
Power Supply Unit incl.	No
Connection Cable Secondary	Yes
Secondary Connection	Open cables
Secondary Cable Length	0.24 m
Dimmable	Yes
Control	Dimmable via optional controller
Motion Detector	No

Diameter	110 mm
Installation Depth	68 mm
Cut Out Diameter	95 mm
Product weight	400 g
Working Temperature	-5 to 40 °C
Storage Temperature	-10 to 40 °C
IP Protection Class	IP 20
Life Time L70 / B50	30000 h
Switching Cycles	15000
Power Consumption EEI	16 kWh/1000h G

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	710 lm
Luminous Efficiency	44.4 lm/W
Rated Angle of Reflection	60 Degree
Distribution Characteristic 120°	DLS

Swivel Angle	25 Degree
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Height	70 mm
---------------	-------

