



Special features

- Including 2 plastic panes transparent/satin-finished
- High colour reproduction value

Housing Material	Aluminium
Housing Color	White
Material of Lens	Plastic
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant current
Rated Input	18.5 W
Rated Power Consumption Standby	0.5 W
Rated Input Voltage	34.8 V/DC
Rated Current	500 mA
Power Supply Unit incl.	No
Connection Cable Secondary	Yes
Secondary Connection	Open cables
Secondary Cable Length	0.2 m
Dimmable	Yes
Control	Dimmable via optional power supply unit
Motion Detector	No
Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	90
Rated Luminous Flux	1360 lm
Luminous Efficiency	73.5 lm/W
Rated Angle of Reflection	60 Degree
Distribution Characteristic 120°	DLS
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below
Height	69 mm
Diameter	145 mm

Installation Depth	69 mm
Cut Out Diameter	130 mm
Product weight	546 g
Working Temperature	-5 to 40 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 20
Life Time L70 / B50	40000 h
Switching Cycles	100000
Power Consumption EEI	20 kWh/1000h G

