



Special features

- High colour reproduction value

Housing Material	Aluminium
Housing Color	White
Material of Lens	Plastic
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant current
Rated Input	26 W
Rated Power Consumption Standby	0.5 W
Rated Input Voltage	37 V/DC
Rated Current	700 mA
Power Supply Unit incl.	No
Connection Cable Secondary	Yes
Secondary Connection	Open cables
Dimmable	Yes
Control	Dimmable via optional power supply unit
Motion Detector	No

Cut Out Diameter	200 mm
Product weight	643 g
Working Temperature	-5 to 40 °C
Storage Temperature	-10 to 40 °C
IP Protection Class	IP 20
Life Time L70 / B50	30000 h
Switching Cycles	15000
Power Consumption EEI	26 kWh/1000h G

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	2680 lm
Luminous Efficiency	103.1 lm/W
Rated Angle of Reflection	100 Degree
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Height	38 mm
Diameter	230 mm
Installation Depth	36 mm

