



Special features

- High light emission angle
- Flat installation height

Housing Material	Aluminium
Housing Color	White
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant current
Rated Input	13 W
Rated Power Consumption Standby	0.5 W
Rated Input Voltage	36-37 V/DC
Rated Current	350 mA
Power Supply Unit incl.	No
Connection Cable Secondary	Yes
Secondary Connection	Open cables
Dimmable	Yes
Control	Dimmable via optional power supply unit
Motion Detector	No

Installation Depth	20 mm
Cut Out Length	155 mm
Cut Out Width	155 mm
Product weight	360 g
Working Temperature	-5 to 40 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 20
Life Time L70 / B50	50000 h
Switching Cycles	100000
Power Consumption EEI	13 kWh/1000h G

Light Source	LED, Light source not changeable
Color Temperature	2700 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	1000 lm
Luminous Efficiency	76.9 lm/W
Rated Angle of Reflection	110 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Length	180 mm
Width	180 mm
Height	21 mm