



Special features

- High colour reproduction value

Housing Material	Aluminium
Housing Color	White
Material of Lens	Plastic
Functions	HCL
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant voltage
Rated Input	15 W
Rated Power Consumption Standby	0.5 W
Rated Input Voltage	24 V/DC
Power Supply Unit incl.	No
Connection Cable Secondary	Yes
Secondary Connection	Open cables
Dimmable	Yes
Control	Dimmable via optional controller
Motion Detector	No

Cut Out Diameter	222 mm
Product weight	538 g
Working Temperature	-5 to 40 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 20
Life Time L70 / B50	50000 h
Switching Cycles	100000
Power Consumption EEI	14 kWh/1000h G

Light Source	LED, Light source not changeable
Colour Temperature	2700-6000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	940 lm
Luminous Efficiency	62.7 lm/W
Rated Angle of Reflection	115 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Height	20 mm
Diameter	236 mm
Installation Depth	20 mm