




LED PANEL 8 + 16


- Can be individually combined with power supply unit [excl.]
- suitable for 24 V HCL control units

Housing	Aluminium	Control	Dimmable via optional controller
Colour Temperature	2700-6000 K	Colour Rendering Index (Ra)	80
Rated Input Voltage	24 V/DC		
Power Supply Unit incl.	No		
Light Beam Angle	115 Degree		


Article	Housing Color		Luminous Flux	Ø cut out	Ø	Power	Installation Depth	Price
565102	<input type="checkbox"/> White		470 lm	135 mm	145 mm	8.5 W	18 mm	€ 55.95
565103	<input type="checkbox"/> White		940 lm	222 mm	236 mm	15.0 W	20 mm	€ 85.95



Accessories


843501 RF-smart, Starter-Set LED Single/CCT, 12-48V, 20A remote control incl.  **€ 99.95**

Accessories for 565102

862166 BASIC, CV, Q8H-24-100W  **€ 96.95**

862233 FLAT, CV, UT24V/12W  **€ 21.95**

Accessories for 565103

862168 BASIC, CV, Q8H-24-150W  **€ 129.95**

862234 FLAT, CV, UT24V/20W  **€ 25.95**



Lighting design

Interested in our lighting design service?

Your contact person will be happy to answer any questions you may have.