



UNI II MAX

- „Glow“ effect on the reflector ring
- Can be rotated and swivelled
- Can be individually combined with power supply unit [excl.]

Housing	Aluminium	Light Beam Angle	36 Degree
Colour Temperature	3000 K	Swivelling Angle	85 Degree
Luminous Flux	2150 lm	Cut Out Ø	155 mm
Height	97 mm	Control	Dimmable via optional power supply unit
Ø	165 mm	Colour Rendering Index (Ra)	90
Power	24 W	Rated Current	700 mA
Rated Input Voltage	34-35 V/DC		
Power Supply Unit incl.	No		
Installation Depth	100 mm		

Article	Housing Color		Price
565344	<input type="checkbox"/> White		€ 149.95
565351	<input checked="" type="checkbox"/> Black		€ 149.95



Accessories

930390	Reflector 24° for Uni II Max		€ 10.95
930391	Reflector 36° for Uni II Max		€ 12.95
930392	Reflector 48° for Uni II Max		€ 10.95
930395	Cover heatsink white for series Uni II Max		€ 10.95
930396	Cover heatsink black for series Uni II Max		€ 10.95
930397	Reflector ring white for series Uni II Max		€ 12.95
930398	Reflector ring black for series Uni II Max		€ 10.95
930399	Reflector ring gold for series Uni II Max		€ 14.95
862198	BASIC, CC, V8-30-700mA/30W		€ 26.95
862208	BASIC, DIM, CC, D70040NTF/40W		€ 46.95
862192	BASIC, DIM, Multi CC, IE-45D		€ 69.95